

[54] METHODS AND APPARATUS FOR
EFFICIENT RESOURCE ALLOCATION

[75] Inventor: Narendra K. Karmarkar, Somerset,
N.J.

[73] Assignee: American Telephone and Telegraph
Company, AT&T Bell Laboratories,
Murray Hill, N.J.

[21] Appl. No.: 725,342

[22] Filed: Apr. 19, 1985

[51] Int. Cl.⁴ G06F 15/20; H04Q 3/66;
H04M 7/00

[52] U.S. Cl. 364/402

[58] Field of Search 364/402; 379/113, 221;
340/524

[56] References Cited

U.S. PATENT DOCUMENTS

4,364,115 12/1982 Asai 364/765
4,479,176 10/1984 Grimshaw 369/168
4,481,600 11/1984 Asai 364/765

OTHER PUBLICATIONS

Linear Programming and Extensions, G. B. Dantzig,
1963.

Hacijan, L. G., A Polynomial Algorithm in Linear
Programming, Soviet Math. Dokl, vol. 20, #1, 1979.

Bland, R. G. et al., The Ellipsoid Method: A Survey,
vol. 29, No. 6, Operations Research 1981.

A New Polynomial-Time Algorithm for Linear Pro-
gramming, N. Karmarkar, ACM 1984.

Design and Optimization of Networks with Dynamic
Routing, G. R. Ash et al., The Bell System Tech. Jour-
nal, vol. 60, No. 8, 10/1981, p. 1787.

G. R. Ash et al., Servicing and Real-Time Control of

Networks with Dynamic Routing, The Bell System
Tech. Journal, vol. 60, No. 8, 10/1981, p. 1821.

"The Ellipsoid Method and its Consequences in Combinatorial Optimization," Combinatorica 1(2), Grötschel et al., 1981, pp. 169-197.

Primary Examiner—Joseph Ruggiero

Assistant Examiner—Charles B. Meyer

Attorney, Agent, or Firm—Robert O. Nimtz; Henry T.
Brendzel

[57] ABSTRACT

A method and apparatus for optimizing resource allocations is disclosed which proceeds in the interior of the solution space polytope instead of on the surface (as does the simplex method), and instead of exterior to the polytope (as does the ellipsoid method). Each successive approximation of the solution point, and the polytope, are normalized such that the solution point is at the center of the normalized polytope. The objective function is then projected into the normalized space and the next step is taken in the interior of the polytope, in the direction of steepest-descent of the objective function gradient and of such a magnitude as to remain within the interior of the polytope. The process is repeated until the optimum solution is closely approximated. The optimization method is sufficiently fast to be useful in real time control systems requiring more or less continual allocation optimization in a changing environment, and in allocation systems heretofore too large for practical implementation by linear programming methods.

36 Claims, 5 Drawing Sheets

